

US006084855A

United States Patent [19]

Soirinsuo et al.

[11] Patent Number:

6,084,855

[45] Date of Patent:

Jul. 4, 2000

[54] METHOD AND APPARATUS FOR PROVIDING FAIR TRAFFIC SCHEDULING AMONG AGGREGATED INTERNET PROTOCOL FLOWS

[75] Inventors: Timo Soirinsuo, Cambridge, Mass.;
Outi Markki, Espoo, Finland

[73] Assignee: Nokia Telecommunications, OY, Espoo, Finland

[21] Appl. No.: 08/802,451
[22] Filed: Feb. 18, 1997

[56] References Cited

U.S. PATENT DOCUMENTS

5,278,830 1/1994 Kudo	370/412
5,499,238 3/1996 Shon.	
5,717,858 2/1998 Shtayer	et al 395/200.11
5,828,653 10/1998 Goss .	
5,872,771 2/1999 Park et a	1 370/252

FOREIGN PATENT DOCUMENTS

0 763 915 A2 3/1997 European Pat. Off. .

WO 97/13346 4/1997 WIPO . WO 98/26510 6/1998 WIPO .

OTHER PUBLICATIONS

P. Newman et al., "Flow Labelled IP: A Connectionlness Approach to ATM", Proc. IEEE Infocom, Mar. 1996, Ch. 5-6, pp. 1255-1260.

Primary Examiner—Ajit Patel Attorney, Agent, or Firm—Altera Law Group, LLC

7] ABSTRACT

A method and apparatus is disclosed for providing fair traffic scheduling of L2 connections based on the number of IP flows and a priority coefficient for flow groups in the L2 connection. IP flows are scheduled according to a priority coefficient. The system identifies a number of IP flows for a plurality of connections, assigns a priority coefficient for each of the IP flows and schedules the IP flows according to the priority coefficient. The assignment of a priority coefficient results in a probability P_i that a data unit belonging to a flow carried over connection A_i will be selected for forwarding as defined by $\sigma_i^* \times_{i/2} (x_1 \dots x_n)$, $i = \{1, 2, \dots n\}$, where x_i is the number of flows carried over connections. The relationship between the number of flows x_i and the priority σ_i is defined by $\sum_{(e^{-1}-n)} (\sigma_i^* \times_i) / \sum_{(i-1-n)} x_i = 1$.

32 Claims, 6 Drawing Sheets

